

Silwet[™] 408 Super Spreader

Description

Silwet 408 super spreader is a trisiloxane ethoxylate based adjuvant that lowers the surface tension of spray solutions beyond that which is achievable with conventional nonionic surfactants.

Key Features and Typical Benefits

- Super spreader for soluble liquid and emulsifiable concentrate formulations
- Promotes spray volume reduction
- Promotes rapid uptake of agrochemicals (rainfastness)
- Can significantly improve spray coverage
- Nonionic
- Meets EPA 40 CFR §180.910 requirements⁽¹⁾
- OMRI Listed for organic use



Typical Physical Properties

Property	Value
Surface Tension mN/m (0.1% wt%)(^a)	21.5
Cloud Point (0.1 wt%), °C	<10
Viscosity (cSt at 25 °C)	35
CMC (Wt%)(^b)	0.007
Pour Point, °C	-8
Specific Gravity at 25 °C	1.020
Flash Point(^c), °C (°F)	118 (244)

Typical properties are average data and are not to be used as or to develop specifications.

Potential Applications and Use Rates

Application	Typical Use Rate
Fertilizers and Micronutrients	0.015% to 0.1%
Fungicide	0.015% to 0.1%
Herbicide	0.025% to 0.15%
Insecticide	0.025% to 0.1%
Plant Growth Regulators	0.025% to 0.1%

Use rates are dependent on crop, agrochemical and spray volume requirements.

(1) The components meet the requirements of U.S. regulation EPA 40 CFR §180.910, and therefore are exempt from tolerances when used as an inert ingredient in agricultural applications in accordance with the other conditions of that regulation

(a) Surface tension by Wilhelmy Plate Method

(b) Critical Micelle Concentration

(c) Pensky-Martens Closed Cup, ASTM Method D93

General Conditions for Use

In Agrochemical In-Can Formulations

Silwet 408 super spreader may be used as a component in agrochemical formulations. Although organosilicone surfactants are subject to hydrolysis under acidic or basic conditions, optimum performance is achieved by buffering the formulation to pH 6.5 to 7.5. Additionally, it is recommended that Silwet 408 super spreader be used at a concentration of at least 5%, based on the total formulation.

As a Tank-Mix Adjuvant

Silwet 408 super spreader, when used as a tank-side adjuvant may be used to improve spray coverage, improve uptake or to allow for a reduction in spray volume. Silwet 408 super spreader is most effective as a tank-side adjuvant when spray mixtures are within a pH range of 5 to 8 and used within 24 hours of preparation.

High spray volumes, coupled with high surfactant rates, are not required to achieve sufficient coverage with Silwet 408 super spreader. In fact, it has the potential to provide adequate coverage in many low volume spray applications at rates between 0.025% and 0.1%.

Patent Status

Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute the permission, inducement or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.

Product Safety, Handling and Storage

Customers should review the latest Safety Data Sheet (SDS) and label for product safety information, safe handling instructions, personal protective equipment if necessary, emergency service contact information, and any special storage conditions required for safety. Momentive Performance Materials (MPM) maintains an around-the-clock emergency service for its products. SDS are available at www.momentive.com or, upon request, from any MPM representative. For product storage and handling procedures to maintain the product quality within our stated specifications, please review Certificates of Analysis, which are available in the Order Center. Use of other materials in conjunction with MPM products (for example, primers) may require additional precautions. Please review and follow the safety information provided by the manufacturer of such other materials.

Limitations

Customers must evaluate Momentive Performance Materials products and make their own determination as to fitness of use in their particular applications.

Contact Information**Email**

commercial.services@momentive.com

Telephone**Americas**

+1 800 295 2392

+1 614 986 2495

Latin America

+55 11 4534 9660

**Europe, Middle East,
Africa and India**

00800 4321 1000

+40 213 044229

Asia Pacific

China

800 820 0202

Japan

+81 276 20 6182

All Other Countries

+60 3 9206 1543

For product prices, availability, or order placement, contact our customer service center by visiting www.momentive.com or emailing commercial.services@momentive.com

DISCLAIMER:

THE MATERIALS, PRODUCTS AND SERVICES OF MOMENTIVE PERFORMANCE MATERIALS INC. AND ITS SUBSIDIARIES AND AFFILIATES (COLLECTIVELY "SUPPLIER"), ARE SOLD SUBJECT TO SUPPLIER'S STANDARD CONDITIONS OF SALE, WHICH ARE INCLUDED IN THE APPLICABLE DISTRIBUTOR OR OTHER SALES AGREEMENT, PRINTED ON THE BACK OF ORDER ACKNOWLEDGMENTS AND INVOICES, AND AVAILABLE UPON REQUEST. ALTHOUGH ANY INFORMATION, RECOMMENDATIONS, OR ADVICE CONTAINED HEREIN IS GIVEN IN GOOD FAITH, SUPPLIER MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, (i) THAT THE RESULTS DESCRIBED HEREIN WILL BE OBTAINED UNDER END-USE CONDITIONS, OR (ii) AS TO THE EFFECTIVENESS OR SAFETY OF ANY DESIGN INCORPORATING ITS PRODUCTS, MATERIALS, SERVICES, RECOMMENDATIONS OR ADVICE. EXCEPT AS PROVIDED IN SUPPLIER'S STANDARD CONDITIONS OF SALE, SUPPLIER AND ITS REPRESENTATIVES SHALL IN NO EVENT BE RESPONSIBLE FOR ANY LOSS RESULTING FROM ANY USE OF ITS MATERIALS, PRODUCTS OR SERVICES DESCRIBED HEREIN. Each user bears full responsibility for making its own determination as to the suitability of Supplier's materials, services, recommendations, or advice for its own particular use. Each user must identify and perform all tests and analyses necessary to assure that its finished parts incorporating Supplier's products, materials, or services will be safe and suitable for use under end-use conditions. Nothing in this or any other document, nor any oral recommendation or advice, shall be deemed to alter, vary, supersede, or waive any provision of Supplier's standard Conditions of Sale or this Disclaimer, unless any such modification is specifically agreed to in a writing signed by Supplier. No statement contained herein concerning a possible or suggested use of any material, product, service or design is intended, or should be construed, to grant any license under any patent or other intellectual property right of Supplier covering such use or design, or as a recommendation for the use of such material, product, service or design in the infringement of any patent or other intellectual property right.

The use of the "™" symbol designates registered or unregistered trademarks of Momentive Performance Materials Inc. or its affiliated companies.

Momentive is a registered trademark of Momentive Performance Materials Inc.



260 Hudson River Road
Waterford, NY 12188 USA
momentive.com